

Ø64

FOCUS50/..
downlight



Light distribution



Project _____

Type _____

Nota _____

Quantity _____

Date _____

Lamp

(Bulb not included)

Lamp type	QR-CB 51
Lamp base	GU5,3/GX5,3
Quantity	1
Power	50W
Voltage	12V

Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø64 mm
Installation depth	70 mm
Dimensions fixture	ø78x60 mm
Spring type	S2 - flat springs
IP protection rating	IP20
Weight	0,1200 kg

Electrical

Connection voltage	~12V
Fixture class	III
Type of transformer	Without transformer
Light source replaceability	Replaceable light source by an end-user













Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____
Type _____
Nota _____
Quantity _____
Date _____

Ø64

FOCUS50/..
downlight

Colours

	1	white gloss	FOCUS50.1
	11	alu grey	FOCUS50.11
	13	bronze	FOCUS50.13
	13M	bronze matt	FOCUS50.13M
	14	alu satin	FOCUS50.14
	16	satin gold	FOCUS50.16
	1M	white texture	FOCUS50.1M
	2	black matt	FOCUS50.2
	2M	black tex	FOCUS50.2M
	4	shiny gold	FOCUS50.4

Options

S6.65/..	plasterkit	PLASTERKIT
----------	------------	------------