


## MONA LISA Ø120

4051/..

pendant + swivel, rod shorten.



### Light distribution



Project \_\_\_\_\_

Type \_\_\_\_\_

Nota \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

### Lamp

(Bulb not included)

Lamp type QT14

Lamp base G9

Quantity 1

Power 20W

Voltage 230V

### Physical

Use type Interior

Fixation type Ceiling suspended

Dimensions fixture ø120x70 mm

Bar Ø8,3 mm

Rod 800 mm

Endtype B3 - swivel

IP protection rating IP20

### Electrical

Connection voltage ~230V

Fixture class I

Light source replaceability Replaceable light source by an end-user



Groendreef 60, 9880 Aalter, Belgium  
T +32 9 374 19 51 - info@psmlighting.be  
www.psmlighting.be

Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## MONA LISA Ø120

4051/..  
pendant + swivel, rod shorten.

### Colours

 2M      black tex      4051.2M

---

### Options

065.D8,3/..    rosette to build in - round - with swivel B3    ROSETTE IN  
033.B3.D8,3/..    built-up base for pendant - round - with swivel B3    ROZET VOOR PENDEL

---