


Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## MAGMA TYPE 3 = even with the floor

3364.X/..

remov. floorlight flush frame



### LED

Lamp type	Led
Quantity	1
Power	4,5W
Current	350mA
Kelvin	
Lumen	720
CRI	83

### Physical

Use type	Interior + exterior
Fixation type	Floor
Type of opening	Rectangle
Aperture dimensions	140x140 mm
Glass thickness	5-9
Installation depth	165 mm
Dimensions fixture	138,5x138,5x165 mm
IP protection rating	IP66

### Electrical

Connection voltage	~230V
Fixture class	I
LED driver	Included
Control gear replaceability	Replaceable control gear by a professional
Light source replaceability	Replaceable (LED only) light source by a professional

### Light distribution





Groendreef 60, 9880 Aalter, Belgium  
T +32 9 374 19 51 - info@psmlighting.be  
www.psmlighting.be

Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## MAGMA TYPE 3 = even with the floor

3364.X/..  
remov. floorlight flush frame

### Colours

### Options

S1138.5.135/..	supplement for floorlight - square cover plate with square glass	Suppl. Larger cover plate
S1138.9.135/..	supplement for floorlight - square cover plate with square glass	Suppl. Larger cover plate