


Ø70 LUXOR.IP20

3394.IP20.S1/..
downlight



Light distribution



Project _____
Type _____
Nota _____
Quantity _____
Date _____

LED

Lamp type	Led
Quantity	1
Power	6,6W
Current	500mA
Kelvin	2700K 4000K
Lumen	965
CRI	83

Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø70 mm
Dimensions fixture	80x80x120 mm
Reflector	ø50 mm
Spring type	S1 - torsion springs
IP protection rating	IP20
Reflector	40°

Electrical

Connection current	=500mA
Fixture class	III
LED driver	Not included
Light source replaceability	Replaceable (LED only) light source by a professional
Energy efficiency	D



Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____
Type _____
Nota _____
Quantity _____
Date _____

Ø70 LUXOR.IP20

3394.IP20.S1/..
downlight

Colours

	14 alu satin	3394.IP20.S1.14.WW WW WW WW NW NW NW NW
	1M white texture	3394.IP20.S1.1M.WW WW WW WW NW NW NW NW
	2M black tex	3394.IP20.S1.2M.WW WW WW WW NW NW NW NW