


LUXOR BOMBA.IP20

1392.IP20.S1/..
downlight



Light distribution



Project _____
Type _____
Nota _____
Quantity _____
Date _____

LED

Lamp type	Led
Quantity	1
Power	9,5W
Current	700mA
Kelvin	2700K 3000K
Lumen	1300
CRI	83

Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø100 mm
Installation depth	140 mm
Dimensions fixture	ø109x120 mm
Reflector	Ø70 mm
Spring type	S1 - torsion springs
IP protection rating	IP20
Reflector	40°

Electrical

Connection current	=700mA
Fixture class	III
LED driver	Not included
Light source replaceability	Replaceable (LED only) light source by a professional
Energy efficiency	D



Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____

Type _____

Nota _____

Quantity _____

Date _____

LUXOR BOMBA.IP20

1392.IP20.S1/..
downlight

Colours

	14 alu satin	1392.IP20.S1.14.WW WW WW NW NW NW
	1M white texture	1392.IP20.S1.1M.WW WW WW NW NW NW
	2M black tex	1392.IP20.S1.2M.WW WW WW NW NW NW