


**Ø80**

PICO500OUT/..  
downlight



### Light distribution



Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

### Lamp

(Bulb not included)

Lamp type	QR-CB 51
Lamp base	GU5,3/GX5,3
Quantity	1
Power	50W
Voltage	12V

### Physical

Use type	Interior + exterior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø80 mm
Installation depth	65 mm
Dimensions fixture	ø89x55 mm
Spring type	S2 - flat springs
IP protection rating	IP20
Weight	0,1759 kg

### Electrical

Connection voltage	~12V
Fixture class	III
Type of transformer	Without transformer
Light source replaceability	Replaceable light source by an end-user

## Ø80

PICO500UT/..  
downlight

### Colours

	20	raw brass	PICO500UT.20
	21A	rust ano	PICO500UT.21A
	31MA	white texture ano	PICO500UT.31MA
	31MX	white texture	PICO500UT.31MX
	32A	black texture ano	PICO500UT.32A
	32X	black texture	PICO500UT.32X
	37A	grey texture ano	PICO500UT.37A
	46A	grey-brown ano	PICO500UT.46A
	46X	grey-brown	PICO500UT.46X
	5	inox 316	PICO500UT.5
	5B	inox 316 1x coated	PICO500UT.5B
	5BB	inox 316 2x coated	PICO500UT.5BB

### Options

S1/..	supplement - set torsion springs	SET TORSION SPRINGS
300V.12V/..	supplement for downlight - waterproof fitting - without LED driver	FITTING IP54