

Project \_\_\_\_\_

Type \_\_\_\_\_

Nota \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

## Ø82 EQUAL CLICK SYSTEM CONCRETE

E-RING-CONCRETE/..

built-in ring



### Physical

Use type	Interior
Type of opening	Round
Aperture dimensions	Ø82 mm
Installation depth	80 mm
Dimensions fixture	Ø82x65 mm
IP protection rating	IP20
Weight	0,1600 kg

### Electrical



Groendreef 60, 9880 Aalter, Belgium  
T +32 9 374 19 51 - info@psmlighting.be  
www.psmlighting.be

Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## Ø82 EQUAL CLICK SYSTEM CONCRETE

E-RING-CONCRETE/..  
built-in ring

### Colours

no colour                      E-RING-CONCRETE

---

### Options

E- COVER/..	built-in cassette - reusable cover	EQUAL CLICK SYSTEM
E- CALIBER/..	caliber - reusable caliber for placing ring in concrete or gyproc ceiling	EQUAL CLICK SYSTEM

---