

Groendreef 60, 9880 Aalter, Belgium T +32 9 374 19 51 - info@psmlighting.be www.psmlighting.be

Project	
Туре	
Nota	
Quantity	
Date	


# **NOVA FLAT LED SB+DIVA + DRIVER**

444.10013/.. downlight





## **Light distribution**



#### LED

Lamp type	Led
Quantity	1
Power	6W
Current	120mA
Kelvin	2700K   3000K
Lumen	450
CRI	98

## **Physical**

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø80 mm
Installation depth	45 mm
Dimensions fixture	100x100x35 mm
Spring type	S2 - flat springs
Directional	In both planes
IP protection rating	IP20
Reflector	36°
Weight	0,3275 kg

#### **Electrical**

Connection voltage	~230V
Fixture class	II
LED driver	Included
Dimmable	Led C
Control gear replaceability	Replaceable control gear by a professional
Light source replaceability	Replaceable (LED only) light source by a professional
Energy efficiency	G



Groendreef 60, 9880 Aalter, Belgium T +32 9 374 19 51 - info@psmlighting.be www.psmlighting.be

Project	
Туре	
Nota	
Quantity	
Date	

### **NOVA FLAT LED SB+DIVA + DRIVER**

444.10013/.. downlight

#### **Colours**



14 alu satin 444.10013.14.WW | WW | WW | NW | NW | NW | WW



1M white texture 444.10013.1M.WW | WW | WW | NW | NW | NW | NW | WW



2M black tex 444.10013.2M.WW | WW | WW | NW | NW | NW | WW

### **Options**

S1/	supplement - set torsion springs	SET TORSION SPRINGS
NOVA.D15/	accessory for downlight - Lens 15°	NOVA LED LENS
NOVA.D60/	accessory for downlight - Lens 60°	NOVA LED LENS