

NORA AC

AC.700.10016/..
downlight



Light distribution



Project _____
Type _____
Nota _____
Quantity _____
Date _____

LED

Lamp type	Led
Quantity	1
Power	9,5W
Voltage	230V
Kelvin	2700K 3000K 4000K
Lumen	700
CRI	92


Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø80 mm
Installation depth	140 mm
Dimensions fixture	ø87x130 mm
Spring type	S2 - flat springs
IP protection rating	IP20
Reflector	36°
Weight	0,3109 kg

Electrical

Connection voltage	~230V
Fixture class	I
Dimmable	Led C
Light source replaceability	Replaceable (LED only) light source by and end user
Energy efficiency	G

Instructies aansluiting








Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____
Type _____
Nota _____
Quantity _____
Date _____

NORA AC

AC.700.10016/..
downlight

Colours

	14 alu satin	AC.700.10016.14.WW CW NW
	1M white texture	AC.700.10016.1M.WW CW NW
	2M black tex	AC.700.10016.2M.WW CW NW

Options

S1/.. supplement - set torsion springs SET TORSION SPRINGS