

LIPSTICK by SUMUM

1906/..

spotlight with flexible tube



Light distribution



Project	
Type	
Nota	
Quantity	
Date	

LED

Lamp type	Led
Quantity	1
Power	1,7W
Current	500mA
Kelvin	2950K
Lumen	168
CRI	80

Physical

Use type	Interior
Fixation type	Wall
Dimensions fixture	ø60x453 mm
Base	Ø60xH65 mm
Head	Ø20xH88 mm
Flex	300 mm
Directional	In both planes
IP protection rating	IP20
Reflector	25°
Weight	0,4250 kg

Electrical

Connection voltage	~230V
Fixture class	I
LED driver	Included
Dimmable	Not dimmable
Control gear replaceability	Replaceable control gear by a professional
Light source replaceability	Replaceable (LED only) light source by a professional
Energy efficiency	F



Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____

Type _____

Nota _____

Quantity _____

Date _____

LIPSTICK by SUMUM

1906/..
spotlight with flexible tube

Colours

	16 satin gold	1906.16.WW WW WW WW WW WW WW
	162 black - gold	1906.162.WW WW WW WW WW WW WW
	1M white texture	1906.1M.WW WW WW WW WW WW WW
	216 black - gold	1906.216.WW WW WW WW WW WW WW
	2M black tex	1906.2M.WW WW WW WW WW WW WW

Options

S1537/..	switching module - supplement switch	LIPSTICK SWITCH
----------	--------------------------------------	-----------------