

Groendreef 60, 9880 Aalter, Belgium T +32 9 374 19 51 - info@psmlighting.be www.psmlighting.be


MYLA JACOB | DALI ADAPTOR

8584.3974.300/.. built-up spot with adaptor





Light distribution



Project	
Туре	
Nota	
Quantity	
Date	

LED

Lamp type	Led
Quantity	1
Power	5,8W
Current	500mA
Kelvin	2700K 3000K
Lumen	555
CRI	90

Physical

Fixation type Ceiling Dimensions fixture Ø40x345 mm	ре
Dimensions fixture ø40x345 mm	n type
	sions fixture
Head Ø40xH300 mm	
Directional In both planes	onal
IP protection rating IP20	ection rating
Reflector 48°	tor

Electrical

Fixture class Dimmable Dali Control gear replaceability Light source replaceability Energy efficiency Control gear replaceability Replaceable (LED only) light source by a professional	Connection voltage	48V-DC
Control gear replaceability Replaceable control gear by a professiona or psmlighting Light source replaceability Replaceable (LED only) light source by a professional	Fixture class	III
Control gear replaceability or psmlighting Light source replaceability Replaceable (LED only) light source by a professional	Dimmable	Dali
Light source replaceability professional	Control gear replaceability	Replaceable control gear by a professional or psmlighting
Energy efficiency G	Light source replaceability	
	Energy efficiency	G



Groendreef 60, 9880 Aalter, Belgium T +32 9 374 19 51 - info@psmlighting.be www.psmlighting.be

Project	
Туре	
Nota	
Quantity	
Date	

MYLA JACOB | DALI ADAPTOR

8584.3974.300/.. built-up spot with adaptor

Colours

	1M white texture	8584.3974.300.1M.NW NW NW NW WW WW WW
	29 black - gold in	8584.3974.300.29.NW NW NW NW WW WW WW
	2M black tex	8584.3974.300.2M.NW NW NW NW WW WW WW
	49 white - gold in	8584.3974.300.49.NW NW NW WW WW WW WW