

## JACOB PENDEL

3973.500/..  
pendant



### Light distribution



Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

### LED

Lamp type	Led
Quantity	1
Power	5,6W
Current	500mA
Kelvin	2700K   3000K
Lumen	639
CRI	80

### Physical

Use type	Interior
Fixation type	Ceiling suspended
Dimensions fixture	ø40x500 mm
Cable	1500 mm
Endtype	Textile cable
IP protection rating	IP20
Reflector	35°
Weight	0,5000 kg

### Electrical

Connection current	=500mA
Fixture class	III
LED driver	Not included
Light source replaceability	Replaceable (LED only) light source by a professional
Energy efficiency	E
CIE flux code	93 98 100 100 100













Groendreef 60, 9880 Aalter, Belgium  
T +32 9 374 19 51 - info@psmlighting.be  
www.psmlighting.be

Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## JACOB PENDEL

3973.500/..  
pendant

### Colours

	14 alu satin		TX11 alu grey	3973.500.14.TX11.WW   NW
	1M white texture		TX1 white	3973.500.1M.TX1.WW   NW
	29 black - gold in		TX2 black	3973.500.29.TX2.WW   NW
	2M black tex		TX2 black	3973.500.2M.TX2.WW   NW
	49 white - gold in		TX1 white	3973.500.49.TX1.WW   NW

### Options

TR89800256/.. driver - LCBI | 15W - 500mA | leading and trailing edge DRIVER 500mA