

INCA

1475/..
downlight



Light distribution



Project _____

Type _____

Nota _____

Quantity _____

Date _____

Lamp

(Bulb not included)

	Lamp 1	and Lamp 2
Lamp type	QR-LP111	PAR 36
Lamp base	G53	screw
Quantity	1	1
Power	50W	50W
Voltage	12V	50W

Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	ø162 mm
Installation depth	100 mm
Dimensions fixture	ø180x80 mm
Spring type	S1 - torsion springs
Directional	In both planes
IP protection rating	IP20
Weight	0,4750 kg

Electrical

Connection voltage	~12V
Fixture class	III
Type of transformer	Without transformer
Light source replaceability	Replaceable light source by an end-user



Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____
Type _____
Nota _____
Quantity _____
Date _____

INCA

1475/..
downlight

Colours

	14	alu satin	1475.14
	1M	white texture	1475.1M
	2M	black tex	1475.2M

Options

1808B/..	plasterkit - square	OLIVIA-INCA plasterkit
----------	---------------------	------------------------