


Ø80

HERO.ES50/..
downlight



Light distribution



Project _____
Type _____
Nota _____
Quantity _____
Date _____

Lamp

(Bulb not included)

Lamp type	QPAR 51
Lamp base	GU10
Quantity	1
Power	20W
Voltage	230V

Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø80 mm
Installation depth	120 mm
Dimensions fixture	100x100x110 mm
Spring type	S2 - flat springs
IP protection rating	IP20
Weight	0,2000 kg

Electrical

Connection voltage	~230V
Fixture class	I
Light source replaceability	Replaceable light source by an end-user



Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____

Type _____

Nota _____

Quantity _____

Date _____

Ø80

HERO.ES50/..
downlight

Colours

	1	white gloss	HERO.ES50.1
	11	alu grey	HERO.ES50.11
	14	alu satin	HERO.ES50.14
	1M	white texture	HERO.ES50.1M
	2	black matt	HERO.ES50.2
	2M	black tex	HERO.ES50.2M

Options

S6.80/..	plasterkit	PLASTERKIT
----------	------------	------------