


OBELIX

3191/..
downlight for veranda profiles



Light distribution



Project _____
Type _____
Nota _____
Quantity _____
Date _____

LED

Lamp type	Led
Quantity	1
Power	3,4W
Voltage	24V-DC
Kelvin	2800K 4000K 6500K
Lumen	150
CRI	80


Physical

Use type	Interior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø40 mm
Installation depth	50 mm
Dimensions fixture	44x44x38 mm
Spring type	S1 - torsion springs
IP protection rating	IP44
Reflector	43°
Weight	0,1400 kg

Electrical

Connection voltage	=24V-DC
Fixture class	III
Type of transformer	Without transformer
Light source replaceability	Non-replaceable light source
Energy efficiency	G

Instructies aansluiting





Groendreef 60, 9880 Aalter, Belgium
T +32 9 374 19 51 - info@psmlighting.be
www.psmlighting.be

Project _____
Type _____
Nota _____
Quantity _____
Date _____

OBELIX

3191/..
downlight for veranda profiles

Colours

-  14 alu satin **3191.14.NW | NW | WW | WW | CW | CW | NW | WW | CW**
-  1M white texture **3191.1M.NW | NW | WW | WW | CW | CW | NW | WW | CW**
-  2M black tex **3191.2M.NW | NW | WW | WW | CW | CW | NW | WW | CW**

Options

- TR122442/.. transformer - DC SLIM/U | 13W - 24VDC TRANSFO 24V
- TR122434/.. transformer - DC SLIM/U IP65 | 13W - 24VDC TRANSFO 24V