


## OBELIX

W3191/..  
downlight for veranda profiles



### Light distribution



Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

### LED

Lamp type	Led
Quantity	1
Power	3,4W
Voltage	24V-DC
Kelvin	2800K   4000K   6500K
Lumen	150
CRI	80


### Physical

Use type	Interior + exterior
Fixation type	Ceiling
Type of opening	Round
Aperture dimensions	Ø40 mm
Installation depth	50 mm
Dimensions fixture	44x44x38 mm
Spring type	S1 - torsion springs
IP protection rating	IP54
Reflector	43°

### Electrical

Connection voltage	=24V-DC
Fixture class	III
Type of transformer	Without transformer
Light source replaceability	Non-replaceable light source
Energy efficiency	G

Instructies aansluiting





Groendreef 60, 9880 Aalter, Belgium  
T +32 9 374 19 51 - info@psmlighting.be  
www.psmlighting.be

Project \_\_\_\_\_  
Type \_\_\_\_\_  
Nota \_\_\_\_\_  
Quantity \_\_\_\_\_  
Date \_\_\_\_\_

## OBELIX

W3191/..  
downlight for veranda profiles

### Colours

	31MA white texture ano	W3191.31MA.WW   CW   NW
	32A black texture ano	W3191.32A.WW   CW   NW

### Options

TR122442/..	transformer - DC SLIM/U   13W - 24VDC	TRANSFO 24V
TR122434/..	transformer - DC SLIM/U IP65   13W - 24VDC	TRANSFO 24V